

Kino8 2K7

Amplifiers

A new generation with a very high capacity of instantaneous power and high efficiency audio modules in class D with an excellent quality of sound.

State-of-the-art amplification technology applied in the most efficient and eco-friendly possible way. These are the basis on which this new series was developed, which is capable of offering the most optimal solution to the very exigent fixed-installations market.

Hi audio quality in an extremely efficient class D design
 Ultra light weight 5.5kg, compact package 35cm deep
 Up-side-down design to avoid fan dust accumulation
 Industry standard Barrier Strips and Phoenix connectors
 Detented sealed potentiometers
 Optionally tamper proof potentiometers



OUTPUT POWER

20Hz-20kHz, 0.1% THD

@2 Ω	@4 Ω	@8 Ω	Bridge @4 Ω	Bridge @8 Ω
-	8x250W	8x180W	-	4x500W

Output Power

Continuous Average Power
 RMS, 1kHz, 1.0% THD+N

@2 Ω	-
@4 Ω	8x310W
@8 Ω	8x210W
Bridge @4 Ω	-
Bridge @8 Ω	4x620W
Pink Noise 12dB Crest Factor	
@2 Ω	-
@4 Ω	8x340W
@8 Ω	8x225W

Frequency Response

Power Bandwidth ±0.25dB	20Hz-20kHz.
-------------------------	-------------

Phase Response

@ 1 watt 20Hz-20kHz	+15 deg
---------------------	---------

Total Harmonic Distortion

20Hz-20kHz	<0,05%
------------	--------

Damping Factor

20Hz-500Hz @8 Ω	>400
-----------------	------

Intermodulation Distortion

SMPTE	-
-------	---

Crosstalk

20Hz-1kHz	>75 dB
-----------	--------

Voltage Gain

	32 dB
--	-------

Sensitivity

Rated Power @8 Ω	2,0 V
------------------	-------

Signal-to-Noise-Ratio

Unweighted	
A weighted	101 dBA

Required AC Mains

230 V - 0.5 A (idle)

@4 Ω (1/8 rated power)	4,5 A
@8 Ω (1/8 rated power)	

Dimensions

W x H x D (mm)	483× 89× 350
W x H x D (inches)	19 × 3,5 × 13,8

Weight

Net	5 Kg/11 Lbs.
-----	--------------