

LW 5115 / LW 5115-BI

Screen systems

BASS:	1 x 15" speaker with 2,5" voice coil
MID:	1 x 8" speaker with 1,46" voice coil
TREBLE:	1 x 1" driver with 1" PM4 voice coil
HORN:	90° x 40° for mid-high range LW 5115 HFD-HFM with pan/tilt adjustment
POWER:	5115 570W AES/1140Prg. 5115BI 400+170W AES/800+340W Prg. Nominal impedance 8+8 ohm.
SENSITIVITY:	LF unit: Sens 96,5dB/1W/1m. Half space SPL 121,9dB MF/HF unit: Sens 94dB/1W/1m. Free field SPL 116,3dB
FREQUENCY RESPONSE:	(-10dB) 32,8 to 19.000 Hz.
SIZE:	158 x 66 x 27 cm.



This is our shallow profile 3 way system, introduced back in Barcelona CineEurope 2013. Is is a "low cost" version of our LW 5115, a 3 way system for biamp with built-in network, shallow profile. 1 x 15" loudspeaker + 1 x 8" loudspeaker + 1,1" PM4 driver. With a new pan/tilt aiming device for the mid-high horn designed for small space behind the screen. The system is fitted with our new SCD (screen compensation device). All of the three transducers are in phase. To save labour costs, it is delivered pre assembled in two cartons.

Presets for installation:

- X-over, 200 Hz
- Phase not inverted
- No delays

EQ for medium/treble unit:

- EQ1: 1.500Hz/Q1.8 -4dB
- EQ2: 2.700Hz/Q2 -4dB
- No EQ for bass unit

