

## LW 7011 V2

## Surround systems

BASS:	1 x 10" speaker with 1,5" voice coil
MID:	
TREBLE:	1 x 1" driver with 1" voice coil
HORN:	100° x 60° constant coverage biradial horn LW7011HFD
POWER:	180W AES/360 W Prg. Nominal Impedance 8 ohm.
SENSITIVITY:	97,4dB/1W/1m. Free field SPL 118,5dB SPL 121,5dB with musical criteria
FREQUENCY RESPONSE:	28 Hz.-18.000 Hz.
SIZE:	46 x 46 x 25,5 (12,5) cm.



The V2 of this system has an improved acoustic enclosure. With a special treatment, the frequency of resonance of the system is now lower. This permits to the installer to EQ in a wider range of frequencies.

This concept of light ABS surround speaker. 10" + 1" + constant bi-radial horn for medium and big cinemas, is very easy to install in the walls of the cinemas because of its extremely low weight, with the fixed support.

This model is also intended for ceiling speaker for Dolby Atmos (property of Dolby Laboratories) or Barco Auro (property of Barco) with the optional LW 7712 Support. As it is manufactured in plastic ABS, it can be mounted in open air cinemas. It is fitted also with a receipt for 35 mm. normalized tripod size.

