

LW 8001-BI V2

Screen systems

| | |
|---------------------|---|
| BASS: | 2 x 15" speaker with 2,5" voice coil |
| MID: | 2 x 6" speaker with 1,46" voice coil |
| TREBLE: | 2 x 1" driver with 1" voice coil |
| HORN: | 2 x Isophasic ABS horns, 140° x 12° each. With pan/tilt adjustment. |
| POWER: | Bass system, 500W AES/1000W Prg. 4 ohm. Medium/treble system 310W AES/620W Prg. 4 ohm. |
| SENSITIVITY: | LF Unit: 100dB/1W/1m. - SPL 127dB - SPL 130dB with musical criteria MHF unit: 95dB/1W/1m. - SPL 120dB - SPL 123dB with musical criteria |
| FREQUENCY RESPONSE: | 37/22.000 Hz. For bi-amp cut off frequency use a single crossover working at 150Hz. We recommend using our LW 8080 processor, which is delivered with all necessary presets. |
| SIZE: | 144,7 x 66 x 60,4 cm. |



A screen system including LAT2014 (Line Array Technology), which combines professional compression drivers with true isophasic horns to achieve an extreme -3dB coverage throughout the whole audience area. 2 x 15" bass section plus a middle-treble section with Line Array Technology and 2 x 6" medium drivers plus 2 x 1" compression drivers + 2 x isophasic horns. We strongly recommend this model as the natural replacement to our discontinued products LW 2203-BI and LW 5107-BI.

