

LW 8002-BI

Screen systems

BASS:	2 x 15" speaker with 3" voice coil
MID:	3 x 6" speaker with 1,46" voice coil
TREBLE:	3 x 1" driver with 1" voice coil
HORN:	3 x Isophasic ABS horns, 140° x 12° each. With pan/tilt adjustment.
POWER:	Bass system, 800W AES/1600W Prg. 4 ohm. Medium/treble system 465W AES/930W Prg. 5 ohm.
SENSITIVITY:	LF unit: 101dB/1W/1m. Half space - SPL 130dB - SPL 133dB with musical criteria MHF unit: 97dB/1W/1m. half space - SPL 124dB - SPL 127dB with musical criteria
FREQUENCY RESPONSE:	35,5/22.000 Hz. For biamp cut off freq. please use our LW-8080 DSP Processor
SIZE:	161,3 x 66 x 61,2 cm.



A screen system including LAT2014 (Line Array Technology), which combines professional compression drivers with true isophasic horns to achieve an extreme -3dB coverage throughout the whole audience area. 2 x 15" bass section plus a middle-treble section with Line Array Technology and 3 x 6" medium drivers plus 3 x 1" compression drivers + 3 x isophasic horns. For the biamp cut off frequency, please use our LW-8080 DSP Processor, which is delivered with all necessary presets, or a single crossover working at 200Hz. We strongly recommend this model as the natural replacement to our discontinued products LW 2105-BI, LW 5201-BI and LW 5019HD.

