

## LW 8007-TRI

## Screen systems

BASS:	4 x 15" speaker with 4" voice coil
MID:	10 x 6" speaker with 1,46" voice coil
TREBLE:	10 x 1" driver with 1" voice coil
HORN:	6+4 x Isofasic ABS horns, 140° x 12° each. With pan/tilt adjustment.
POWER:	Bass system, 2800W AES/5600W Prg. 4+4 ohm. 6 units medium/treble system 930W AES/1860W Prg. 4 ohm. 4 units Medium/treble system 620W AES/1240W Prg. 4 ohm.
SENSITIVITY:	Complete assembly: SPL 133dB - SPL peak 136dBÂ LF Unit: Sens. 104dB 1W/1m. Half space - SPL 135,8dB - SPL 138,8dB with musical criteria MHF 6 units: Sens. 101,5dB 1W/1m. Free field - SPL 130,3dB - SPL 133,3dB with musical criteria MHF 4 units: Sens. 98,7dB 1W/1m. Free field - SPL 126dB - SPL 129dB with musical criteria
FREQUENCY RESPONSE:	24/22.000 Hz. For biamp cut off freq. please use our LW-8080 DSP Processor
SIZE:	284,8 x 132Â x 61,6 cm.

Screen system with LAT2014 technology, which combines professional compression drivers with true isophasic horns to achieve an extreme coverage of -3dB throughout the whole audience area.

Some medium-treble units can be added with different settings for a perfect coverage in really big auditoriums with separate amplifiers.

For the biamp cut off frequency, please use our LW-8080 DSP Processor, which is delivered with all necessary presets, or a single crossover working at 150Hz.

